


2xOF302-40B (oil-less)

Voltage	V	100	100	120	200	200	230	230	3x400	3x440		
Frequency	Hz	50	60	60	50	60	50	60	50	60		
Motor	HP	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2		
	kW	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9		
Displacement	l/min	216	276	276	216	276	216	276	216	276		
	CFM	7.63	9.75	9.75	7.63	9.75	7.63	9.75	7.63	9.75		
FAD @ 8 bar	l/min	76	88	88	76	88	76	88	76	88		
	CFM	2.68	3.11	3.11	2.68	3.11	2.68	3.11	2.68	3.11		
Max. pressure	bar	8	8	8	8	8	8	8	8	8		
	psi	120	120	120	120	120	120	120	120	120		
Max. current	A	15.0	17.4	13.2	8.2	9.2	6.8	8.2	2.8	2.8		
Tank size	litres	40	40	40	40	40	40	40	40	40		
	gallon	10.6	10.6	10.6	10.6	10.6	10.6	10.6	10.6	10.6		
Weight	kg	46	46	46	46	46	46	46	46	46		
	lbs	101	101	101	101	101	101	101	101	101		
Noise level	dB(A)/1m	68	69	69	68	69	68	69	68	69		
Thermal protection		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes		
Duty cycle		100%	100%	100%	100%	100%	100%	100%	100%	100%		



Dimensions (l x w x h)
420 x 540 x 620 mm / 16⁴/₈ x 21²/₈ x 24³/₈ inch

Technical modifications reserved

JUN-AIR®

E-mail: info@jun-air.dk
Internet: www.jun-air.com

